

# H-702

- Premium closed shoulder design for long-haul application
- Solid shoulder provides superior stability and resistance to irregular wear
- Rib sipes increase wet traction



Item	Tire Size, Load Range, & Service Description		PR	Ship Weight (lbs.)	Meas. Rim Width (inches)	Tread Depth (32 <sup>nds</sup> )	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Min Dual Spacing	Eclipse Code
------	--	--	----	--------------------------	--------------------------------	--	----------------------	---------------------	------------------------	-----------------------	------------------	---------------------	---------------------	-----------------

## H-702

59969	11R22.5	BLK	146/143L	16	124	8.25	26	6005	120	6610	120	10.94	41.81	12.52	59969
59536	295/75R22.5	BLK	144/141L	14	121	8.25	26	5675	110	6175	110	10.83	40.47	12.52	59536
59972	11R24.5	BLK	149/146L	16	134	8.25	26	6610	120	7160	120	10.94	43.86	12.52	59972
59535	285/75R24.5	BLK	144/141L	14	126	8.25	26	5675	110	6175	110	10.83	41.85	12.52	59535
59977	225/70R19.5	BLK	128/136L	12	69	6.75	20	3415	95	3640	95	8.62	32.24	10	59977
59978	245/70R19.5	BLK	133/131L	14	78	7.5	21	4300	110	4540	110	9.57	33.35	10.98	59978
59533	11R22.5	BLK	144/142L	14	127	8.25	26	5842	104	6173	104	10.94	41.81	12.52	59533
59534	11R24.5	BLK	146/143L	14	134	8.25	26	6008	104	6614	104	10.94	43.86	12.52	59534