

H-902

- Regional all position rib tire for both steer & trailer application
- Wide 5-rib design delivers long mileage & shoulder wear resistance on steer axle use
- Designed with lower rolling resistance to provide better fuel efficiency



Item	Tire Size, Load Range, & Service Description		PR	Ship Weight (lbs.)	Meas. Rim Width (inches)	Tread Depth (32 ^{nds})	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Min Dual Spacing	Eclipse Code
------	--	--	----	--------------------	--------------------------	----------------------------------	----------------	---------------	------------------	-----------------	---------------	------------------	------------------	--------------

H-902

**59220	11R22.5	BLK	144/142M	14	107	8.25	14	5840	105	6175	105	10.94	41.3	12.52	59220
59217	225/70R19.5	BLK	128/126L	14	65	6.75	16	3750	110	3970	110	8.62	32.01	10	59217
59216	245/70R19.5	BLK	133/131L	14	74	7.5	17	4300	110	4540	110	9.57	33.07	10.98	59216
59545	215/75R17.5	BLK	135/133L	16	56	6	16	4540	125	4805	125	8.07	30.39	9.33	59545
59546	235/75R17.5	BLK	143/141L	16	63	6.75	17	5675	125	6005	125	8.9	31.57	10.31	59546
59219	255/70R22.5	BLK	140/137L	16	93	7.5	17	5070	120	5510	120	9.65	36.73	11.3	59219
59979	275/70R22.5	BLK	148/145M	16	102	8.25	19	6395	125	6490	125	10.71	37.91	12.24	59979
**64369	11R22.5	BLK	146/143M	16	107	8.25	14	6005	120	6610	120	10.94	41.3	12.52	64369

**Tread pattern varies